


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 17/04, H04N 7/18, A61B 17/12, 1/005	A2	(11) International Publication Number: WO 99/47050 (43) International Publication Date: 23 September 1999 (23.09.99)
(21) International Application Number: PCT/US99/06085 (22) International Filing Date: 19 March 1999 (19.03.99) (30) Priority Data: 60/078,916 20 March 1998 (20.03.98) US (71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US]; One Scimed Place, Maple Grove, MN 55311-1566 (US). (72) Inventors: KORTENBACH, Juergen, A.; 990 Apache Street, Miami Springs, FL 33166 (US). SATER, Ghaleb; 1200 Salem Street #123, Lynnfield, MA 01954 (US). MCBRAYER, Michael, Sean; 4044 Park Avenue, Miami, FL 33133 (US). GELLMAN, Barry, N.; 19 Pebblebrook Road, North Easton, MA 02356 (US). (74) Agent: FORCIER, John, V.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: ENDOSCOPIC SUTURE SYSTEMS  (57) Abstract <p>A surgical instrument for applying sutures to tissue includes a <u>needle deployment mechanism (127)</u> and a <u>catch mechanism (129)</u>. In some embodiments, the needle deployment mechanism (127) employs a linear path. Alternatively, it can employ a curved needle. The surgical instrument may include a rotatable head (124), a bend (122), and/or a malleable elongated body member formable into various shapes.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

ENDOSCOPIC SUTURE SYSTEMS

Cross-Reference to Related Application

This incorporates by reference, and claims priority to, and the benefit of, provisional U.S. patent application serial number 60/078,916, which was filed on March 20, 1998.

Technical Field

5 The invention generally relates to surgical instruments for applying sutures to tissue. More particularly, the invention relates to needle deployment mechanisms and catch mechanisms.

Background Information

10 Suturing of body tissue is a time consuming aspect of many surgical procedures. For many surgical procedures, it is necessary to make a large opening in the human body to expose the area that requires surgical repair. There are instruments available that allow for viewing of certain areas of the human body through a small puncture wound without exposing the entire body cavity. These instruments, called endoscopes, can be used in conjunction with specialized surgical instruments to detect, diagnose and repair areas of the body that previously required open surgery to access.

15 Currently, most surgical instruments used in endoscopic procedures are limited by the manner in which they access the areas of the human body in need of repair. In particular, the instruments may not be able to access tissue or organs located deep within the body or that are in some way obstructed. Also, many of the instruments are limited by the way they grasp tissue, apply a suture, or recapture the needle and suture. In addition, many of the instruments are
20 complicated and expensive to use due to the numerous parts and/or subassemblies required to make them function properly.

Summary of the Invention

The present invention generally is directed to medical instruments for inserting a suture through body tissue in a quick and easy manner using needle deployment mechanisms and catch

- 2 -

mechanisms. In some embodiments, the needle deployment mechanism employs a linear needle path. In other embodiments, the needle deployment mechanism employs a curved needle path. Some embodiments of the needle deployment and catch mechanism include a rotatable head.

The instruments of the present invention are useful for application of sutures to approximate the sides of a tissue wound in; for example, open, mini-incision, trans-vaginal, or endoscopic surgical procedures. These instruments may be used in surgical procedures such as burch colposuspension, sacrospinous vaginal vault suspension, paravaginal repair, radical prostatectomy, sub-urethral sling, oophorectomy, myomectomy, nissen fundoplication, cholecystectomy, and urethral anastomosis, for example.

In one aspect, the invention relates to a suturing instrument comprising an elongated body member, a head, and a needle carrier. The head extends from a distal end of the elongated body member, and the head defines a longitudinal groove and an opening in communication with the longitudinal groove. The head also includes a needle catch disposed within the opening. The needle carrier is for holding a needle, and the needle carrier is disposed and movable within the longitudinal groove to advance linearly the needle into the opening and towards the needle catch.

Embodiments according to this aspect of the invention can include the following features. The needle carrier can define a needle holder and a recess for suture material. The needle carrier can include a U-bend. The needle catch can include an opening with at least two flexible edges. The suturing instrument can include a handle located opposite the distal end of the elongated body member, and the handle can include an actuator coupled to the needle carrier.

In another aspect, the invention relates to a suturing instrument comprising an elongated body member, a needle catch, and a needle carrier. The needle catch includes at least one opening for receiving a needle, and the needle catch is movable from within the elongated body member to outside of the elongated body member. The needle carrier is for holding the needle, and the needle carrier is movable from within the elongated body member to outside of the elongated body member.

Embodiments according to this aspect of the invention can include the following features. The suturing instrument can include a pusher movably disposed within the elongated body member and coupled to the needle carrier and needle catch. The suturing instrument can also

- 3 -

include a needle catch driver coupled to the pusher and the needle catch and/or a needle carrier driver coupled to the pusher and the needle carrier. The pusher can move the needle carrier and needle catch from within the elongated body member to outside the elongated body member. The pusher can move the needle carrier and needle catch towards each other, and in one embodiment, the needle carrier and needle catch can intersect. In addition, the suturing instrument can include a distal end with an inner taper to direct the needle carrier and needle catch towards each other when moved from within the elongated body member to outside the elongated body member. The needle carrier can include a needle holder and a recess for suture material located at its distal end. The needle catch can include a point for tissue penetration.

10 In yet another aspect, the invention relates to a suturing instrument comprising an elongated body member, a curved needle, and a pusher. The elongated body member includes a distal portion and defines a curved channel within the distal portion. The curved needle includes a series of notches and is receivable within the curved channel. The pusher is movably disposed within the elongated body member and contacts the notches of the needle to advance the needle out of the curved channel.

Embodiments according to this aspect of the invention can include the following features. The curved channel and/or the curved needle can comprise a semi-circular shape. The series of notches disposed on the curved needle can be located on the needle's concave or convex surface. The suturing instrument can define an opening leading to the curved channel and a protruding edge at the opening for engaging the series of notches of the needle.

25 In still another aspect, the invention relates to a suturing instrument comprising an elongated body member and a head. The elongated body member includes a first engaging element located at its distal end. The head includes a second engaging element located at its proximal end that engages with the first engaging element of the elongated body member to position the head in one of a plurality of orientations with respect to the elongated body member.

Embodiments according to this aspect of the invention can include the following features. The first engaging element can include a female configuration, and the second engaging element can include a male configuration for mating with the first engaging element. Alternatively, the first engaging element can include a male configuration and the second engaging element can

- 4 -

include a female configuration for mating with the first engaging element. The female configuration can include a series of notches and/or a flexible detent for engaging the male configuration, and the male configuration can include a series of protuberances, notches, and/or fluted cuts for engaging the female configuration. The head of the suturing instrument can be
5 secured in position by engaging the first and second engaging elements, and the head can be rotated when the first and second engaging elements are disengaged. Alternatively, the head can be positioned by rotating one engaging element with respect to the mating engaging element, and in this configuration the head is secured in place by mechanical engagement of the two engaging elements. The head can be rotated with respect to the body member in increments as small as
10 10°. The head can include a needle deployment mechanism and a catch mechanism located at its distal end, and the distal end can be bullet-shaped to maintain a body lumen in a dilated state.

Additional embodiments according to any of the foregoing aspects of the invention can include the following features. The elongated body member of the suturing instrument can be adapted to access remote tissue or organs within the body. The elongated body member can
15 include a bend or bends. The bend can take the shape of an elbow, a soft curve, a double curve, or any other shape suited to access remote organs or tissue within the body. The elongated body member can be preshaped and permanently bent and comprised of sturdy or resilient material. The elongated body member can also be comprised of a malleable material and thus be bent and shaped to a desired form. The shaping can be done manually outside the body, or remotely within
20 the body to fit the required course for the instrument.

In still yet another aspect, the invention relates to a needle catch for use with a suturing instrument. The needle catch includes at least one opening for receiving a needle, and the needle catch includes a point for tissue penetration. The point can be formed by at least two tapered edges. The needle catch can also be bent to include convex and concave surfaces, and the needle
25 catch can comprise stainless steel.

These and other objects, along with advantages and features of the present invention herein disclosed, will become apparent through reference to the following description of embodiments of the invention, the accompanying drawings, and the claims.

- 5 -

Brief Description of the Drawings

In the drawings, like reference characters generally refer to the same parts throughout the different figures. Also, the drawings are not to scale; emphasis instead generally being placed upon illustrating the principles of the invention.

5 FIG. 1A is a top view of the distal end of one embodiment of the suturing system according to the invention.

FIG. 1B is a side view of the distal end of one embodiment of the suturing system according to the invention featuring a Z-bend needle catch.

10 FIG. 1C is a longitudinal section view of the distal end of one embodiment of the suturing system according to the invention taken along line C-C.

FIG. 1D is a side view of an embodiment of a needle and suture for use with the invention.

FIG. 2A is a schematic representation of one embodiment of the invention for suturing transversely positioned tissue.

15 FIG. 2B is another schematic representation of one embodiment of the invention for suturing transversely positioned tissue.

FIG. 3A is a section view of the distal end of the suturing system of the embodiment shown in FIGS. 2A and 2B in the retracted position.

FIG. 3B is a section view of the distal end of the suturing system of the embodiment shown in FIGS. 2A and 2B in the extended position.

20 FIG. 4 is a perspective view of one embodiment of a needle catch for use with the suturing system of FIGS. 2 and 3.

Fig. 5A is a longitudinal section view of the distal end of one embodiment of the suturing system of the invention.

25 Fig. 5B is a cross-section view of the distal end of one embodiment of the suturing system of the invention taken at line B-B.

- 6 -

FIG. 5C is a side view of one embodiment of a needle with suture.

FIG. 5D is a perspective side view of one embodiment of a pusher.

FIGS. 6A-6C are schematic, perspective, side-view representations of one embodiment of the suturing system of the invention featuring an elbow-shaped, elongated body member with a rotatable head shown in various rotated positions, but not showing a needle deployment mechanism or a needle catch mechanism.

FIGS. 6D-6F are schematic representations of some details of the rotatable head shown in FIGS. 6A-6C and featuring a needle deployment mechanism, a needle catch mechanism, and the engaging elements.

FIG. 7A is a schematic representation of one embodiment of a suturing system of the present invention featuring an elbow-shaped, elongated body member with a rotatable suturing head used in connection with a grasper.

FIG. 7B is a schematic representation of one embodiment of a suturing system of the present invention showing a sectional view of the grasper in the extended position.

FIG. 7C is a schematic representation of one embodiment of a suturing system of the present invention shown located in the urethra and bladder.

Description

In general, the present invention is directed to various improvements of components and mechanisms of needle deployment systems for suturing devices, such as those disclosed in U.S. Patent No. 5,713, 910 to Gordon et al., U.S. Patent No. 5,578,044 to Gordon et al., U.S. Patent No. 5,575,800 to Gordon, U.S. Patent No. 5,540,704 to Gordon et al., U.S. Patent No. 5,458,609 to Gordon et al., and U.S. Patent No. 5,364,408 to Gordon, all of which are incorporated herein by reference in their entirety.

Referring to FIGS. 1A and 1B, the distal end 10 of one embodiment of a suturing system according to the present invention defines a distal longitudinal groove 12 located at the tip 14 of the distal end 10 and intersecting with the distal wall 16 of an opening 18. The suturing system

- 7 -

can include a handle located opposite the distal end of the elongated body member. The handle could take a variety of forms, for example, the handle could be one of the types used with Boston Scientific Corporation suturing systems, in particular the Laurus-Capio Push & Catch suturing system. The distal end 10 may be fabricated from molded or machined plastic material such as polycarbonate or glass-filled polycarbonate. Located within the opening 18 and in a plane substantially perpendicular to the needle carrier 44 path is a needle catch 20 having a distal side 22 resting on the floor 24 of the opening 18 and a proximal side 26 resting against the proximal wall 28 of the opening 18. Between the two sides 22 and 26, the needle catch 20 forms a concave bend 30 proximal to side 22 and a convex bend 32 proximal to side 26 forming a Z-like shape. Between the two sides 22 and 26 of the needle catch 20 and aligned with the distal longitudinal groove 12 is an opening 34 formed by two flexible edges 36 and a mouth 38. The lateral sides 40 of the needle catch 20 wrap around the distal end 10 of the suturing system and are secured in place by notches 42 turned inward into the body of the distal end, or alternatively into small grooves. The needle catch 20 is preferably made of thin stainless steel material, in particular, high temper stainless steel. The needle catch may be manufactured by stamping, laser machining or chemical etching, for example.

Referring to FIG. 1C, in the longitudinal groove 12 is positioned a needle carrier 44 having a convex U-bend 46. At the end 48 of the needle carrier is a needle holder 50 that defines a hole with a recess 52 for lodging the needle 54 and suture 56. When the needle carrier 44 is actuated along the longitudinal axis of the elongated body member, the needle carrier 44 advances the needle 54 linearly from the distal end of the longitudinal groove 12, through the tissue located within the opening 18, and into the needle catch 20. The release of the needle 54 from the needle carrier 44 occurs upon reverse motion of the needle carrier 44.

Referring to FIG. 1D, suitable needles 54 for positioning into the needle holder 50, include a neck 58 with a hole at one of its ends for inserting a suture 56 and at least one shoulder 60. The body 62 of the needle 54 is tapered from the shoulder 60 to the point 64 to facilitate tissue penetration and insertion into the opening 34 of the needle catch 20. The shoulders 60 are made of larger dimensions than the opening 34 of the needle catch 20. During insertion of the needle 54 into the opening 34 of the needle catch 20, the edges 36 of the opening 34 flex upon pressure exerted by the body 62 of the needle 54 at the shoulders 60 and permit entry of the needle 54 into the opening 34. The needle 54 is retained within the needle catch 20 when the edges 36 return to

- 8 -

their original position once the shoulders 60 have entered the opening 34 and the neck 58 of the needle 54 is lodged in the opening 34. Preferably, the neck 58 has smaller dimensions than the opening 34 to permit the edges 36 to return to their original position. The needle 54 is released from the needle catch 20 by sliding the neck 58 of the needle 54 toward the mouth 38 of the opening 34. The dimensions of the mouth 38 are larger than the dimensions of the shoulders 60 to permit the release of the needle 54 from the needle catch 20.

Needle deployment/catch systems as described in FIGS. 1A-1C can be made with various dimensions as necessary for a specific application. In particular, this instrument is well suited to being made to minute dimensions. For example, suitable dimensions to use for a instrument for performing an urethral anastomosis can be as follows: the tip 14 may be 1.15 in. long, 0.205 inch wide, and 0.275 in. high; the distal end 10 may be 0.058 in. in diameter; the needle carrier 44 may be 0.032 in. in diameter; the distance between the distal wall 16 of the opening 18 to the opening 30 of the needle catch 20 may be 0.15 in. long.

One advantage of the suturing system/instrument of FIGS. 1A-1D is that it requires fewer parts; thereby, making it easier and less expensive to manufacture than known devices.

Referring to FIGS. 2A and 2B, in another embodiment of the suturing instrument 66 according to the present invention, the instrument is configured to deploy a needle 54 through tissue 68 positioned substantially perpendicular to the elongated body member 82 of the suturing instrument 66. The suturing instrument comprises a pusher 72 having a knob 74 at the proximal end and an elongated portion 76 extending from the knob 74 to the distal end and connected to the needle carrier driver 78 and the needle catch driver 80. The elongated portion 76 of the pusher 72 is positioned within an elongated body member 82, which includes a tubular body 70 that extends from the proximal end to the distal end where it contacts the tissue 68 to be sutured. The elongated body member 82 includes a handle portion 84 located at the proximal end that provides grip for manipulation of the instrument and support for actuating the pusher 72.

In the retracted position, as shown in FIG. 2A, the tissue 68 to be sutured is positioned at the distal end of, and substantially perpendicular to, the elongated body member 82. The needle carrier 44 and the needle catch 20 are positioned within the elongated body member 82, and the knob 76 is afar from the handle portion 84 of the elongated body member 82. In an extended

- 9 -

position, as shown in FIG. 2B, the needle carrier 44 holding a needle 54 and the needle catch 20 are moved to a position outside the elongated body member 82 and into the tissue 68. The needle carrier 44 and the needle catch 22 can be moved simultaneously by the needle carrier driver 78 and the needle catch driver 80 when actuated by the pusher 72. The needle carrier 44 and the needle catch 22 meet afar from the distal end of the elongated body member and into the tissue 68 such that the needle 54 with a suture 56 attached thereto is pushed through the opening 34 of the needle catch 20 until the shoulders 60 of the needle 54 snap there through. In the extended position, the knob 74 of the pusher 72 is proximal to, and in contact with, the handle 84 of the elongated body member 82. The suture 56 and the needle 54 are brought back out of the tissue 68 with the needle catch 20 when the suturing system is returned to its retracted position. To facilitate return to the retracted position, the knob 74 of the pusher 72 may alternatively comprise a ring for insertion of a finger by the operator of the instrument.

Referring to FIGS. 3A and 3B, showing a longitudinal section of the distal end of a particular embodiment of a suturing instrument 66, the interior wall 86 of the elongated body member 82 tapers inward at the distal end. When the pusher 72 is depressed, moving from afar towards the handle 84, the elongated portion of the pusher 72 pushes simultaneously the needle carrier driver 78 and the needle catch driver 80 towards their extended position. The tapered interior wall 86 directs both, the needle carrier 44 and the needle catch 20 towards each other when pusher 72 is depressed.

Alternatively, the needle carrier driver 78 and needle catch 80 can be prebent or include a pivotal system such as a pivot pin or scissors so that the paths of the needle carrier 44 and the catch 20 run from separated lateral positions within the elongated body member 82 to an intersecting point outside the elongated body member 82. In the fully extended position, shown in FIG. 3B, the needle 54 has been pushed through the opening 34 of the needle catch 20 within the tissue 68 to be sutured. When the suturing instrument 66 is returned to its retracted position, as shown in FIG. 3A, the needle 54 is retained by the needle catch 20 and drawn out of the tissue 68. The needle 54 can then be released from the needle catch 20 by pulling the needle 54 and cutting the suture 56 off.

A needle catch 20, suitable for use in the suturing instrument 66 shown in FIGS. 2A and 2B, is shown in FIG. 4. The needle catch 20 is preferably made of a sheet of stainless steel which

- 10 -

is bent to provide a concave surface 88 and a convex surface 90 for rigidity. The needle catch 20 can contain several openings 34. The needle catch 20 also comprises two tapered sides 92 that merge into a point 94 for easy penetration of tissue 68. The needle catch 20 can be mounted and secured to the needle catch driver 80 either by permanent bond using glue or any known
5 interlocking system such as pressure snap-in.

Referring to FIGS. 5A-5D, in another embodiment of the invention the suturing instrument includes an elongated body member 82 having a channel 96 extending from the head portion to the distal end. FIG. 5A shows a longitudinal sectional view of the distal end of the suturing instrument 66 with the distal end of channel 96 intersecting tangentially with a curved
10 guiding channel 98. The guiding channel 98 is positioned along the longitudinal axis of the elongated body member 82 and defines two openings 100, 102 on the lateral side of the elongated body member 82. The proximate opening 100 permits ingress of a needle 104 (shown in FIG. 5C) having a curved shape and a series of notches 106 on a portion of the convex surface 108. The point 110 of the needle having smooth surfaces and being tapered to facilitate penetration of
15 tissue 68. The tail 112 of the needle 104 having a hole to permit fixation of the suture material 56.

Referring to FIGS. 5A and 5B, a pusher 114 is positioned in the longitudinal channel 96 with the head 116 forming an edge to provide support and engage into the notches 106 of the needle 104 introduced into the guiding channel 98.

On the outer wall 118 of the distal opening 102 is positioned a protruding edge 120 that provides for locking of the needle 104 during egress from the guiding channel 98. Each push of the pusher 114 moves the needle 104 within the guiding channel 98 from the proximal opening 100 to the distal opening 102 until a notch 106 locks onto the protruding edge 120. A pull of the pusher 114 slides the head 116 of the pusher 114 against the sliding sides of the
20 notches 106 until it engages in a notch 106 closer to the tail 112 of the needle. The push and pull motion is repeated several times until all of the needle 104 has passed through the guiding channel 98, and into tissue positioned parallel to, and in contact with, the distal opening 102. The needle 104 can then be extracted from the tissue once the point 110 resurfaces out of the mass of the tissue with surgical pliers, tweezers, hemostats, needle holders, or other appropriate surgical
25 instrument.
30

- 11 -

FIG. 5B shows a cross-sectional view of the distal end of the suturing instrument at the intersection between the longitudinal channel 96 and the guiding channel 98.

FIG. 5D shows a prospective view of the pusher 114 with the head 116.

In yet another embodiment, the instrument can be adapted to facilitate access into the abdominal cavity and the placement of suture(s) radially in a body lumen. Such instrument may be particularly useful where anastomosis is required such as urethral anastomosis following radical prostatectomy or in blood vessel or bowel anastomosis. Referring to FIGS. 6A-6C, the suturing instrument 66 includes an elongated body member 82 and a rotatable head 124. The elongated body member 82 can include an elbow 122 (or bend). The head 124 rotates by angular increments. The elongated body member 82 includes an engaging element located at its distal end 128. The head 124 includes an engaging element located at its proximal end 126 for mating with the engaging element of the elongated body member 82. The head 124 includes a dilator cap or a bullet-shaped end at the distal end 130 of the head 124 to maintain the urethra or any body lumen in a dilated configuration. The rotation of the head 124 is performed manually between each application of a suture in a body lumen and before reloading with the needle and suture to permit application of a series of sutures along the circumference of the lumen, at incremental angular positions that can be as small as 10°. The embodiment of the suturing instrument featuring an elbow and rotatable head is particularly adapted to perform suturing after removal of the prostate to connect the bladder to the urethra or generally following any other type of resection.

In one embodiment, the rotatability of the head 124 is accomplished with the structure depicted in FIGS. 6D-6F. The head 124 includes an engaging element with a male configuration 123. The male configuration 123 includes a series of fluted cuts 133 located along 330° of its perimeter. The male configuration 123 includes a stop to prevent the head from rotating 360°. The elongated body member 82 includes an engaging element with a female configuration 125 and a flexible detent 131. The female configuration 125 is a substantially circular recess with the flexible detent mounted within the elongated body member 82 and protruding into the substantially circular recess. The flexible detent 131 can be a length of spring wire or a pin, and can be made of nitinol. The head 124 can be positioned by rotating the male configuration 123 engaging element with respect to the female configuration 125 engaging element, deflecting the flexible detent 131, and then allowing the flexible detent 131 to mechanically engage the fluted cut

- 12 -

133 which corresponds to the desired angular orientation. The head can be positioned in angular increments of 30°. In addition, the head 124 depicted in FIGS. 6D-6F includes a needle deployment mechanism 127 and a needle catch mechanism 129.

Referring to FIGS. 7A-7C, to further facilitate positioning of the instrument within the
5 body passageway, a grasper device 132 may be introduced into the body cavity by a second point of entry. The grasper device comprises a hollow elongated body member 134 for housing a pair of spring-loaded jaws or tweezers 136 at the distal end of the body member 134. The tweezers 136 are close together in a retracted position as shown in FIG. 7A and open to permit grasping of the knob 138 located on the distal end of the head 124 in an extended position as
10 shown in FIG. 7B. When closed around the ball or knob 138, the grasping tweezers 136 can allow rotatable movement of the knob 138 and thus rotation of the head 124.

The proximal end of the grasper device 132 features a button 140 that is positioned at the proximal end of a wire 142. The wire 142 is connected to the tweezers 136 at the distal end. The device is maintained in the retracted position by a spring 144 located in the head 146 of the
15 grasper 132 which rests its proximal end against the button 140 and its distal end against a protuberance 148 positioned in the interior wall of the head 146.

FIG. 7C shows both the grasper 132 and the suturing instrument 66 located in the urethra 150 and the bladder 152 below the public bone 154 of a male following prostatectomy. The void left by the removed prostate is addressed by using the instrument 66 together with the
20 grasper 132 to insert sutures all around the end of the urethra 150 to join it to the bladder 152.

In yet other embodiments of the instant invention, the aforementioned suturing systems can be used to deploy an anchor or fastener that is to remain in the tissue. Such anchor or fastener may be; for example, a barbed needle, a metal clip, or a staple.

Having described embodiments of the invention, it will be apparent to one skilled in the art
25 that other embodiments incorporating the concepts disclosed herein may be used without departing from the spirit of the invention. Thus, numerous other embodiments include, but are not limited to: changes in the dimensions of the instruments; the type of materials employed; the location and type of needle, anchor or fastener; and needle loading mechanisms. All are within the scope of the present invention. The described embodiments are to be considered in all

- 13 -

respects only as illustrative and not restrictive. Therefore, it is intended that the scope of the present invention be only limited by the following claims.

What is claimed is:

- 14 -

Claims

- 1 1. A suturing instrument, comprising:
2 an elongated body member including a distal end;
3 a head extending from the distal end of the elongated body member, the head
4 defining a longitudinal groove and an opening proximal to the longitudinal groove, the
5 head also includes a needle catch disposed within the opening; and
6 a needle carrier disposed within the longitudinal groove, the needle carrier for
7 holding a needle and being movable within the longitudinal groove to advance the needle
8 linearly into the opening and towards the needle catch.
- 1 2. The suturing instrument of claim 1 wherein the elongated body member includes a
2 bend.
- 1 3 The suturing instrument of claim 1 wherein the elongated body member includes
2 two bends.
- 1 4. The suturing instrument of claim 1 wherein the elongated body member is adapted
2 to access remote organs or tissue within the body.
- 1 5. The suturing instrument of claim 1 wherein the elongated body member comprises
2 a malleable material.
- 1 6. The suturing instrument of claim 1 wherein the needle carrier defines a needle
2 holder.
- 1 7. The suturing instrument of claim 6 wherein the needle holder includes a recess for
2 a suture material.

- 15 -

1 8. The suturing instrument of claim 1 wherein the needle carrier includes a U-bend.

1 9. The suturing instrument of claim 1 further comprising a handle disposed opposite
2 the distal end of the elongated body member and including an actuator, the actuator being
3 coupled to the needle carrier.

1 10. The suturing instrument of claim 1 wherein the needle catch defines an opening
2 including at least two flexible edges.

1 11. A suturing instrument, comprising:

2 an elongated body member;

3 a needle catch including at least one opening for receiving a needle and being
4 movable from within the elongated body member to outside of the elongated body
5 member; and

6 a needle carrier for holding the needle and being movable from within the
7 elongated body member to outside of the elongated body member.

1 12. The suturing instrument of claim 11 wherein the elongated body member includes
2 a bend.

1 13. The suturing instrument of claim 11 wherein the elongated body member includes
2 two bends.

1 14. The suturing instrument of claim 11 wherein the elongated body member is
2 adapted to access remote organs or tissue within the body.

1 15. The suturing instrument of claim 11 wherein the elongated body member
2 comprises a malleable material.

- 16 -

- 1 16. The suturing instrument of claim 11 wherein the needle carrier defines a
2 needle holder.
- 1 17. The suturing instrument of claim 11 wherein the needle catch includes a point for
2 tissue penetration.
- 1 18. The suturing instrument of claim 11 further comprising:
2 a pusher disposed within the elongated body member and coupled to the needle
3 catch and the needle carrier, the pusher being movable within the elongated body member
4 to move the needle catch and needle carrier from within the elongated body member to
5 outside the elongated body member.
- 1 19. The suturing instrument of claim 11 wherein the needle catch and the needle
2 carrier move towards each other.
- 1 20. The suturing instrument of claim 19 wherein the needle catch and needle carrier
2 intersect.
- 1 21. The suturing instrument of claim 11 wherein the elongated body member includes
2 a distal end having an inner taper to direct the needle catch and needle carrier towards
3 each other when moved from within the elongated body member to outside the elongated
4 body member.
- 1 22. A needle catch, comprising:
2 at least one opening for receiving a needle; and
3 a point to permit tissue penetration.
- 1 23. The needle catch of claim 22 wherein the needle catch is bent and includes a
2 convex surface and a concave surface.

- 17 -

- 1 24. The needle catch of claim 22 wherein the point is formed by at least two tapered
2 edges.
- 1 25. The needle catch of claim 22 wherein the needle catch comprises stainless steel.
- 1 26. A suturing instrument, comprising:
2 an elongated body member including a distal portion and defining a curved channel
3 within the distal portion;
4 a curved needle including a series of notches, the curved needle for being received
5 within the curved channel; and
6 a pusher disposed within the elongated body member and being movable within the
7 elongated body member to contact the notches of the needle and advance the needle out
8 of the curved channel.
- 1 27. The suturing instrument of claim 26 wherein the elongated body member includes
2 a bend.
- 1 28. The suturing instrument of claim 26 wherein the elongated body member includes
2 two bends.
- 1 29. The suturing instrument of claim 26 wherein the elongated body member is
2 adapted to access remote organs or tissue within the body.
- 1 30. The suturing instrument of claim 26 wherein the elongated body member
2 comprises a malleable material.
- 1 31. The suturing instrument of claim 26 wherein the curved channel comprises a semi-
2 circular shape.

- 18 -

- 1 32. The suturing instrument of claim 26 wherein the curved needle comprises a semi-
2 circular shape.
- 1 33. The suturing instrument of claim 26 wherein the elongated body member further
2 defines an opening leading to the curved channel and a protruding edge of the opening for
3 engaging the series of notches of the needle.
- 1 34. The suturing instrument of claim 26 wherein the series of notches are disposed on
2 a convex surface of the curved needle.
- 1 35. A suturing instrument, comprising:
2 an elongated body member including a distal end, the distal end including a first
3 engaging element; and
4 a head including a proximal end, the proximal end including a second engaging
5 element to position the head in one of a plurality of orientations with respect to the
6 elongated body member.
- 1 36. The suturing instrument of claim 35 wherein the first engaging element includes a
2 female configuration and the second engaging element includes a male configuration for
3 mating with the first engaging element.
- 1 37. The suturing instrument of claim 35 wherein the first engaging element includes a
2 male configuration and the second engaging element includes a female configuration for
3 mating with the first engaging element.
- 1 38. The suturing instrument of claim 36 or 37 wherein the female configuration
2 includes a series of notches and the male configuration includes a series of protuberances.

- 19 -

- 1 39. The suturing instrument of claim 35 wherein the head is secured in position when
2 the first and second engaging elements are engaged, and rotatable when the first and
3 second engaging elements are disengaged.
- 1 40. The suturing instrument of claim 35 wherein the first engaging element includes a
2 flexible detent and the second engaging element includes a series of fluted cuts.
- 1 41. The suturing instrument of claim 40 wherein the head is positioned by rotating the
2 second engaging element with respect to the first engaging element.
- 1 42. The suturing instrument of claim 40 wherein the head is secured in position by the
2 flexible detent mechanically engaging one of the fluted cuts.
- 1 43 The suturing instrument of claim 35 wherein the plurality of orientations includes
2 increments of 30°.
- 1 44. The suturing instrument of claim 35 wherein the head includes a distal portion for
2 housing a needle deployment and catch mechanism.
- 1 45. The suturing instrument of claim 35 wherein the elongated body member includes
2 a bend.
- 1 46. The suturing instrument of claim 35 wherein the head has a bullet-shaped distal
2 end to maintain a body lumen in a dilated state.




FIG. 1A




FIG. 1B

2/14




FIG. 1D






FIG. 1C






FIG. 3A





FIG. 3B



6/14




FIG. 5C




FIG. 5A




FIG. 5B




FIG. 5D




FIG. 6A




FIG. 6B

9/14




FIG. 6C

10/14





FIG. 6D

11/14



SUBSTITUTE SHEET (RULE 26)

12/14




FIG. 6F




FIG. 7A




FIG. 7B





FIG. 7C



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 17/04, H04N 7/18, A61B 17/12, 1/005, 17/064	A3	(11) International Publication Number: WO 99/47050 (43) International Publication Date: 23 September 1999 (23.09.99)
(21) International Application Number: PCT/US99/06085 (22) International Filing Date: 19 March 1999 (19.03.99) (30) Priority Data: 60/078,916 20 March 1998 (20.03.98) US (71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US]; One Scimed Place, Maple Grove, MN 55311-1566 (US). (72) Inventors: KORTENBACH, Juergen, A.; 990 Apache Street, Miami Springs, FL 33166 (US). SATER, Ghaleb; 1200 Salem Street #123, Lynnfield, MA 01954 (US). MCBRAYER, Michael, Sean; 4044 Park Avenue, Miami, FL 33133 (US). GELLMAN, Barry, N.; 19 Pebblebrook Road, North Easton, MA 02356 (US). (74) Agent: FORCIER, John, V.; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims</i> <i>and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 29 December 1999 (29.12.99)

(54) Title: ENDOSCOPIC SUTURE SYSTEMS**(57) Abstract**

A surgical instrument for applying sutures to tissue includes a needle deployment mechanism (127) and a catch mechanism (129). In some embodiments, the needle deployment mechanism (127) employs a linear path. Alternatively, it can employ a curved needle. The surgical instrument may include a rotatable head (124), a bend (122), and/or a malleable elongated body member formable into various shapes.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

Intern: al Application No

PCT/US 99/06085

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61B17/04 H04N7/18 A61B17/12 A61B1/005 A61B17/064

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61B H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 96 27331 A (YOON INBAE) 12 September 1996 (1996-09-12) page 3, last paragraph -page 4, paragraph 1 page 7, paragraph 2 -page 9, paragraph 2 figures 1,2,5	1,4,6-10
A	figures 5-12	11,26,32
Y	US 5 713 910 A (COOPER ROBERT P ET AL) 3 February 1998 (1998-02-03) column 14, line 38 -column 15, line 41 figures 8A,8B	1,4,6-10
A	US 5 336 229 A (NODA WAYNE A) 9 August 1994 (1994-08-09) figures 1,2	1
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

28 October 1999

Date of mailing of the international search report

10.11.99

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bichlmayer, K-P

INTERNATIONAL SEARCH REPORT

Intern. Application No

PCT/US 99/06085

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 721 099 A (CHIKAMA TOSHIO) 26 January 1988 (1988-01-26) abstract; figure 1 ---	2,3
A	WO 97 15144 A (UROHEALTH SYSTEMS INC ;SHAPIRO STEPHEN J (US); SOSNOWSKI STEPHEN A) 24 April 1997 (1997-04-24) page 4, line 15-17 page 8, line 22 -page 9, line 1 ---	5
A	US 5 364 408 A (GORDON NORMAN S) 15 November 1994 (1994-11-15) figures 6,19 column 7, line 10 -column 8, line 6 ---	11,14, 16,18, 20,26
X	WO 97 47246 A (INFLUENCE MEDICAL TECHNOLOGIES ;SOHN ZE EV (IL)) 18 December 1997 (1997-12-18) figures 9A-9D page 9, line 25 -page 10, line 12 ---	22-25
P,X	US 5 782 845 A (SHEWCHUK DWIGHT) 21 July 1998 (1998-07-21) figure 5 column 4, line 25-61 ---	22-25
A	EP 0 674 875 A (LAURUS MEDICAL CORP) 4 October 1995 (1995-10-04) figures 17A,19 column 24, line 47-58 ---	22-26, 29,31,34
A	WO 92 22041 A (CLINICAL PRODUCT DEV LTD) 10 December 1992 (1992-12-10) figure 1 page 4, last paragraph ---	26
X	EP 0 669 101 A (UNITED STATES SURGICAL CORP) 30 August 1995 (1995-08-30) column 6, line 17-22 column 7, line 24-41 column 14, line 29-37 figures 1,12 ---	35
A	US 5 484 451 A (ASTASHOV VYTCHESALV ET AL) 16 January 1996 (1996-01-16) figure 47 column 18, line 4-37 -----	35

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 99/06085

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐ The additional search fees were accompanied by the applicant's protest.

☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 99/06085

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-10

A suturing instrument comprising an elongated member, a head including a needle catch, and a needle carrier.

2. Claims: 11-21

A suturing instrument comprising an elongated member, a needle catch and a needle carrier.

3. Claims: 22-25

A needle catch.

4. Claims: 26-34

A suturing instrument comprising an elongated body member, a curved needle and a pusher disposed within the body member.

5. Claims: 35-46

A suturing instrument comprising an elongated body member and a head including an engaging element to position the head with respect to said body member.

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern: at Application No

PCT/US 99/06085

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9627331	A	12-09-1996	US 5665096 A	09-09-1997
			AU 5026596 A	23-09-1996
			CA 2214449 A	12-09-1996
			EP 0814707 A	07-01-1998
			JP 10506559 T	30-06-1998

US 5713910	A	03-02-1998	US 5578044 A	26-11-1996
			US 5540704 A	30-07-1996
			US 5458609 A	17-10-1995
			US 5364408 A	15-11-1994
			AU 3512995 A	19-04-1996
			WO 9609796 A	04-04-1996
			US 5741279 A	21-04-1998
			AU 695389 B	13-08-1998
			AU 1343895 A	07-09-1995
			CA 2143012 A	03-09-1995
			EP 0674875 A	04-10-1995
			JP 8033635 A	06-02-1996
			US 5741277 A	21-04-1998
			AU 673692 B	21-11-1996
			AU 5017893 A	29-03-1994
			EP 0738127 A	23-10-1996
			JP 8501005 T	06-02-1996
			WO 9405213 A	17-03-1996
			US 5662664 A	02-09-1997
			US 5700272 A	23-12-1997
			CA 2142965 A	17-03-1995
			US 5575800 A	19-11-1996

US 5336229	A	09-08-1994	AU 6168394 A	29-08-1994
			WO 9417737 A	18-08-1994

US 4721099	A	26-01-1988	NONE	

WO 9715144	A	24-04-1997	AU 7517096 A	07-05-1997

US 5364408	A	15-11-1994	AU 673692 B	21-11-1996
			AU 5017893 A	29-03-1994
			CA 2142965 A	17-03-1994
			EP 0738127 A	23-10-1996
			JP 8501005 T	06-02-1996
			US 5458609 A	17-10-1995
			WO 9405213 A	17-03-1994
			US 5540704 A	30-07-1996
			US 5578044 A	26-11-1996
			US 5575800 A	19-11-1996
			US 5662664 A	02-09-1997
			US 5700272 A	23-12-1997
			US 5713910 A	03-02-1998
			US 5741277 A	21-04-1998
			US 5741279 A	21-04-1998

WO 9747246	A	18-12-1997	AU 2975797 A	07-01-1998

US 5782845	A	21-07-1998	NONE	

EP 0674875	A	04-10-1995	US 5540704 A	30-07-1996
			AU 695389 B	13-08-1998

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Application No

PCT/US 99/06085

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0674875	A	AU 1343895 A	07-09-1995
		CA 2143012 A	03-09-1995
		JP 8033635 A	06-02-1996
		US 5578044 A	26-11-1996
		US 5713910 A	03-02-1998
		US 5741277 A	21-04-1998
		US 5741279 A	21-04-1998

WO 9222041	A 10-12-1992	AU 1783292 A	08-01-1993
		DE 69228747 D	29-04-1999
		EP 0587635 A	23-03-1994
		US 5549619 A	27-08-1996

EP 0669101	A 30-08-1995	US 5520702 A	28-05-1996
		CA 2141913 A	25-08-1995

US 5484451	A 16-01-1996	US 5242457 A	07-09-1993
		AU 688341 B	12-03-1998
		AU 7167594 A	16-03-1995
		CA 2131340 A	04-03-1995
		EP 0641546 A	08-03-1995
		JP 7163576 A	27-06-1995
		US 5573543 A	12-11-1996
